

Check level in battery machine



LIST OF CREDITS

Approximate weight	
Dimensions	
Wide of machine.	1365 mm
High of machine.	2100 mm
Length of machine.	3100 mm
Wide of electrical panel.	
High of electrical panel.	
Length of electrical panel.	
Power supply	
400 Vca / 50 Hz + Neuter + Earth	
Documentation	
Project, manual and declaration of conformity.	
Tack of machine	
6 a 7 bat / min.	

Check level in battery machine

- Machine designed to check level in battery cells, (with measuring resolution of ± 0.5 mm) and blowing in lateral cover holes.
- Measuring of acid level by optical system. Registered by lineal encoder.
- Machine frame constructed in 316 stainless steel and technical plastics such as PVC, polyethylene, polypropylene. etc
- Pneumatic stainless steel FESTO cylinders and antacid coupling.
- Input conveyor belt for EUROBELT / INTRALOX polypropylene.
- RITTAL panel in polyester, KS series, located at the back of the machine.
- Pushbutton enclosure constructed in 316 stainless steel, for controlling movements using the ABB antacid series of controls.
- 5" Monochrome touch screen, for programming and displaying all parameters. This enables the measurement to be calibrated, by introducing real measurements for height between belt and nozzles.
- Program monitoring using PLC SIEMENS S7-series 300.

